

1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2743 2744 2745 2746 2747 2

Page 7

**APPLICATION FOR LETTERS PATENT OF
THE UNITED STATES OF AMERICA**

**For:
METHOD AND APPARATUS FOR DETERMINING
THE ADHESION AND ADHESION LIMIT IN THE
CASE OF VEHICLE TIRES**

**By:
Rolf Gnadler
Hans-Joachim Unrau**

**METHOD AND APPARATUS FOR DETERMINING THE ADHESION AND
ADHESION LIMIT IN THE CASE OF VEHICLE TYRESTIRES**

FIELD OF THE INVENTION

The invention relates to a method and an apparatus for determining the adhesion and/or adhesion limit of a tyretire of a vehicle in motion. In this method and apparatus, the driving state of the vehicle is measured by means
5 of a plurality of driving-dynamics sensors, and the state of the roadway is determined by means of at least one roadway sensor, which detects the state of the roadway. A computer for evaluating the data from the driving-dynamics sensors and the roadway sensor is furthermore provided, the ~~said~~ computer using a driving-dynamics simulation model to determine the kinematic state of
10 the wheel and the adhesion or, taking into account at least one stored tyretire characteristic diagram comprising tyretire characteristics, the adhesion limit.

BACKGROUND OF THE INVENTION

If a vehicle fitted with tyrestires is in a normal driving state involving
15 comparatively low longitudinal and transverse acceleration values, i.e. not in the region of the driving limit, it has hitherto been impossible to draw reliable conclusions about the adhesion and adhesion limit of tyrestires or wheels, of axles or of the vehicle. There is a large degree of uncertainty as to the size of the adhesion reserves, i.e. the gap between the current horizontal forces
20 (circumferential forces and lateral forces) between the tyretire and the roadway (the adhesion) and the maximum forces that can be transmitted (the adhesion limit).

In a normal driving state involving comparatively low longitudinal and transverse acceleration values, it has hitherto only been possible to estimate the adhesion and adhesion limit of production vehicles qualitatively on the basis of the driver's experience, and this only very roughly. With this in mind, the driver can, for example, observe that the roadway is wet and instinctively assume a reduction in the adhesion limit compared with a dry roadway on the basis of his experience. However, this is only partially successful, as demonstrated by the increase in the frequency of accidents on wet roads. On production vehicles, there has hitherto been no facility for determining the adhesion and adhesion limit quantitatively at low longitudinal and transverse accelerations.

It has hitherto also been impossible to provide reliable information on the adhesion and adhesion limit as the vehicle approaches the driving limit, i.e. the adhesion limit, where the longitudinal and transverse acceleration values are comparatively higher. On production vehicles there are known systems such as ABS, ASR or ESP which detect when the vehicle is reaching an adhesion limit or a limit in terms of driving dynamics. However, the adhesion and the adhesion limit are determined neither while the vehicle is in a normal driving state nor as it approaches the driving limit.

In the literature reference H.-J. Görich, System zur Ermittlung des aktuellen Kraftschlußpotentials eines PKW im Fahrbetrieb [System for determining the current adhesion potential of a moving passenger car], Fortschritt-Berichte VDI Series 12, No. 181, VDI-Verlag 1993, Düsseldorf, a proposal is made for a system which allows the adhesion and adhesion limit to be estimated in many cases. Here, driving-dynamics sensors supply

information on the driving state. Roadway sensors, each of which is responsible exclusively for a specific roadway, furthermore supply information on the state of the roadway. In addition, extensive measurements incorporated into ~~tyre~~tire characteristic maps are required for various states of the roadway. Using a simple though not particularly quick vehicle computation model and a vehicle computer which does not allow real-time operation, the current driving state, i.e. the adhesion of the axles and of the vehicle, is compared with the vehicle's adhesion limit determined. The results for the vehicle are represented graphically using a screen in the vehicle.

10 Although the known system supplies information on the adhesion and the adhesion limit of the vehicle, it has various disadvantages.

One disadvantage is that extensive ~~tyre~~tire characteristic maps comprising a multiplicity of ~~tyre~~tire characteristics for all conceivable driving states and states of the roadway are required. These ~~tyre~~tire characteristics are assumed to be invariable. This leads to the results becoming inaccurate as the tread depth decreases during the operation of the vehicle, for example.

In addition, there is the fact that the states of the roadway are divided only relatively roughly into three groups, namely dry, wet and slippery (as in winter). Within a group, the ~~tyre~~tire characteristic maps are assumed to be constant. This likewise leads to, in some cases, very inaccurate results since it is known that, in reality, the depth of water on a wet roadway has a great effect, for example. It is furthermore disadvantageous that the adhesion is determined only for each axle and the adhesion and the adhesion limit are determined for the vehicle. This likewise leads to inaccuracies in determination, especially when the wheels are rolling on different underlying

roadway surfaces. There is thus no possibility of calculating the adhesion separately for each individual wheel.

In the literature reference Th. Dieckmann, Ein neuartiger Ansatz zur Bestimmung der Kraftschlußbedingungen im Reifen/Fahrbahnkontakt, Reifen, 5 Fahrwerk, Fahrbahn [A novel approach to the determination of adhesion conditions in ~~tyretire~~/road contact, ~~tyrestires~~, running gear, roadway], Report on the conference of the VDI-Gesellschaft Fahrzeugtechnik, No. 916, VDI-Verlag, 1991, Düsseldorf, and in document DE 3705983 A1 ("Device for 10 monitoring the utilization factor of the coefficient of road friction prevailing in the braking and/or acceleration of a motor vehicle"), a proposal is made for a method in which conclusions are drawn about the maxima of the circumferential forces that can be transmitted from the initial slope of the circumferential-force/slip curves of the wheels and in which conclusions are drawn therefrom about the adhesion and the adhesion limit of the entire 15 vehicle. This principle is relatively inaccurate and has the following disadvantages.

On the one hand, only the circumferential-force properties of the ~~tyrestires~~ are taken into account, allowing only limited conclusions to be drawn about the lateral-force properties.

20 It has furthermore been found that a sufficiently clear change in the initial slope cannot be recognized in all cases required in practice. Thus, for example, a large difference between the adhesion limits is possible during the transition from a dry roadway to a wet roadway with shallow or moderate water levels, whereas the initial slopes differ only to a small extent.

It is furthermore known that the initial slope of the circumferential-force/slip curves depends not only on the state of the roadway but also on the properties of the ~~tyre~~tires, which change, for example, due to a decrease in the tread depth. Since the stored characteristics are fixed and do not take into
5 account changes in the ~~tyre~~tire properties during operation, it is not possible to draw reliable conclusions about the current adhesion limit from the initial slope.

In document DE 4338587 C2 ("Method for estimating gripping properties of road surface with respect to the wheels of a motor vehicle
10 travelling over it"), the proposal is to measure the torque of the driven wheels and the rotational speed of all the wheels. Moreover, the wheel load acting on the driven wheels is estimated. When the driven wheels reach certain circumferential-slip values and approach the adhesion limit, the current adhesion of the wheels is set to equal the current adhesion limit of the wheels.
15 This is stored in a memory as an instantaneous but temporary estimated value. This stored estimated value is updated as soon as certain conditions are present, if, for example, a driving state involving high circumferential-slip values, in which the adhesion of the wheels is different, is reached again. In this way, the adhesion and adhesion limit of wheels is determined, and it is
20 possible to draw conclusions about the adhesion and adhesion limit of the vehicle.

However, this proposed principle has the disadvantage that sufficiently accurate estimation is only possible if the vehicle comes within the immediate vicinity of the driving limit. In normal driving states, determination cannot be
25 carried out.

The stored adhesion limits can furthermore only be updated if certain criteria, e.g. high circumferential-slip values, are met. Since this is the case only in infrequent driving states, the stored values cannot be updated continuously and thus reliably, despite continuous operation of the system.

5 According to this document, provision is furthermore made for the torque acting on the driven wheels to be measured. This measurement is relatively involved and must operate equally during braking and acceleration. There is furthermore the fact that only the adhesion limit of the tyrestires is estimated, without information on the shape of the full tyretire characteristic
10 being supplied.

The prior art furthermore includes systems which have been investigated within the context of research projects. They allow either only qualitative verdicts on the adhesion and the adhesion limit or, to detect the state of the roadway, require complex sensors which are unsuitable for
15 practical applications or involve unacceptably high costs if used on production vehicles.

~~Taking this prior art as a starting point, the~~ The object on which the invention is based is to provide a method and an apparatus by means of which, ~~as a good~~ an accurate approximation, of the current adhesion and/or
20 the current adhesion limit of a tyretire or of axles of a moving vehicle can be determined in as far as possible for every driving state, ~~that is to say~~ even at comparatively low longitudinal and transverse acceleration values. It should thus be possible to determine the current adhesion limit well before it has been reached. It is furthermore desirable if the associated tyretire
25 characteristic maps can be prepared for a comparatively low outlay.

The invention ~~is thus intended to~~ provides reliable and accurate information on the current adhesion or current adhesion limit in a manner which allows as little outlay as possible. This information can then be made available to the driver, for example, or passed to a system which performs a
5 control intervention in a driving or braking operation.

To achieve this object in the case of a method and an apparatus of the type stated at the outset, the invention provides for the tyretire characteristics (for various states of the roadway and, for example, for various wheel loads) to be adapted to the current tyretire behaviour in the course of operation,
10 starting from an initial set of basic tyretire characteristics.

In the method according to the invention, the current adhesion, in particular the circumferential and lateral forces, and the kinematic state of the wheel, in particular the circumferential-slip and slip angle, are calculated continuously with the aid of the computer, the driving-dynamics simulation
15 model and the signals of the driving-dynamics sensors. The current adhesion limit is furthermore determined by first of all carrying out roadway detection and then selecting associated tyretire characteristics (e.g. for various wheel loads) from a tyretire characteristic-map memory and, finally, after tyretire-characteristic adaptation, determining the current adhesion limit.

20 In this method, the driving-dynamics sensors supply measurement data about the kinematic state of the vehicle and, possibly, about the forces or moments acting on the vehicle. They are used as input variables for the simulation calculations of the computer by means of the driving-dynamics simulation model. The output variables supplied by the simulation calculations
25 are the current adhesion and the kinematic state of the wheels. These

variables constitute output data from the system and can also be used for determining the current adhesion limit.

In principle, the state of the roadway (e.g. dry, wet, snow etc.) can be determined in a manner known per se by means of one or more roadway
5 sensors. However, one disadvantage with this is that the decision as to which state of the roadway is present depends in each case on the correct and reliable operation of a particular specific sensor for the respective state of the roadway or on a particular evaluation variable. If one sensor is malfunctioning or an evaluation variable is incorrect, the corresponding roadway can
10 therefore no longer be identified.

In order to ensure accuracy of determination, the state of the roadway should be detected accurately and reliably. For this purpose, it is proposed, in accordance with a preferred additional feature, that the state of the roadway is determined by means of a plurality of different roadway sensors, the
15 information derived from their signals being evaluated by means of a bound method for delimiting the state of the roadway. In addition to the information on the state of the roadway determined by the roadway sensors, it is also possible for results from the driving-dynamics simulation calculation to be evaluated in the bound method. One example of a piece of information that
20 can be taken into account in the bound method is, for instance, the initial slope of the actual adhesion curve, which can be determined by means of the driving-dynamics simulation calculation.

In the bound method, a multiplicity of pieces of information of different kinds is superimposed, allowing particular states of the roadway to be
25 excluded on the basis of existing combinations of sensor signals or other

information, the correct state of the roadway thus finally being identified as the result of logical combination of the existing information. This is not to be confused with a system incorporating a redundant arrangement of roadway sensors, in which a number of different sensors are intended to sense the same state of the roadway independently of one another. In the bound method that is advantageously employed, different pieces of information are collected and the state of the roadway is inferred by combination of these pieces of information.

If the state of the roadway has been determined by means of the bound method, for example, the associated tyretire characteristic diagram (comprising characteristics for various wheel loads for example) or the associated tyretire characteristic can be selected from a tyretire characteristic-map memory. Selection can be assisted by information from the driving-dynamics sensors. When an apparatus according to the invention is first put into operation, a basic tyretire characteristic diagram containing an initial set of basic tyretire characteristics stored in the computer for a small number of different tyretire/roadway combinations is taken as a starting point.

In the course of the operation of the vehicle, these basic tyretire characteristics are adapted to the current tyretire behaviour by correcting the individual characteristics. This is possible because the system is constructed in such a way that it detects a change in the adhesion behaviour due to a change in tyretire properties, e.g. due to a change in tread depth, in the course of operation from the fact that, in this case, the current adhesion and the kinematic state of the wheels do not match the selected characteristic

diagram or the selected characteristic. The correction can be repeated each time a deviation is detected.

The adaptation of the tyretire characteristics can thus preferably take place when a deviation in the current adhesion in the existing kinematic state of the wheel from the selected tyretire characteristic is detected on the basis of a comparison between the results of the driving-dynamics simulation model and the state of the roadway determined.

The basic tyretire characteristic maps or the tyretire characteristic maps preferably contain only a small total number of tyretire characteristics (for various states of the roadway and, for example, various wheel loads) to be taken into account in the driving-dynamics simulation calculation, preferably fewer than 40, particularly preferably fewer than 20 tyretire characteristics. In accordance with an additional advantageous feature, however, provision can be made for one or more tyretire characteristic maps to be supplemented in the course of operation by tyretire characteristics for further states of the roadway which were not included in the basic tyretire characteristic maps and have proven useful. To this extent, the system can be capable of learning and can be designed to be adaptive.

If it is the case both that the current state of the roadway has been identified and the associated tyretire characteristic has been selected by the system and adapted to the current tyretire behaviour, the adhesion limit can be determined before it has been reached. Using the method according to the invention, it is thus possible to determine the adhesion and adhesion limit more accurately than was hitherto possible. One advantage of the preferred

bound method is that the state of the roadway can be detected more reliably, redundant detection being possible.

In a preferred embodiment of the invention, it is furthermore advantageous that a change in the adhesion behaviour caused by a change in tyretire properties, e.g. by the change in tread depth, in the course of operation can be detected. In addition, only a small number of basic tyretire characteristic maps or basic tyretire characteristics is required and these can be adapted and, if appropriate, supplemented in the course of operation.

According to another advantageous feature, it is proposed that the driving-dynamics simulation model is a real-time model, by means of which the computer calculates the current kinematic state of the wheel and/or the current adhesion and/or the current adhesion limit of the wheel in real time. A driving-dynamics simulation model of this kind, which operates in real time, can be created, for example, by means of rapid, compact differential equations using knowledge on the dynamic behaviour of the vehicle concerned.

If the driving-dynamics simulation model used is designed specifically for real time, the current adhesion calculated in real time using this model and the kinematic state of the wheels can advantageously be used as an input variable for a mechatronic control system which performs control interventions in the handling. If the current adhesion is calculated separately for each wheel, the results can be used, for example, for optimized control of the driving dynamics, thereby making it possible to better ensure the stability of the vehicle in critical driving situations.

These data can also be used in an advantageous manner by mechatronic control systems through determination of the adhesion limit in real time. In this case, for example, a mechatronic brake system can respond more rapidly to changing roadway grip in the event of full braking. If the
5 adhesion limit is determined individually for each wheel, a difference in the grip for the wheels of one axle can be taken into account even as a braking operation is being initiated.

The adhesion and/or the adhesion limit is/are therefore preferably determined for the individual wheels of the vehicle or separately for the
10 wheels of an axle since the kinematic state and critical driving behaviour can thereby be detected more accurately. This provides favourable preconditions for a system which, for example, gives the driver a warning or performs a control intervention in the handling. Determining the adhesion limit separately for individual wheels makes it possible to estimate more accurately whether,
15 owing to different adhesion limits at the individual wheels, critical handling behaviour of the vehicle is to be expected when the vehicle is approaching the driving limit. In this case, it is possible, for example, for a warning to be issued to the driver while the vehicle is still a relatively long way from the driving limit. In the case of individual calculation or evaluation of the wheels of an axle, it is
20 also possible to detect and take account of the case where the wheels have different friction coefficients due, for example, to differences in the state of the roadway.

However, in many embodiments it can also be advantageous if the adhesion and/or the adhesion limit is/are determined for each axle, the wheels
25 of an axle being treated equally, or if the adhesion and/or adhesion limit of the

entire vehicle is determined by means of the particular adhesion values and/or adhesion limits of all the wheels. Calculating the adhesion or adhesion limit of the entire vehicle is suitable for allowing the driving state or driving limit of the vehicle to be described in a simple and easily comprehensible manner. The driver can, for example, be informed during the journey using a suitable representation of the adhesion or adhesion limit.

Within the context of the present invention, it has surprisingly been found that the extremely difficult requirements involved in determining the adhesion or adhesion limit of a ~~tyre~~tire with sufficient accuracy can be met for a relatively low outlay without the need for a high technical outlay involved in providing a multiplicity of ~~tyre~~tire characteristic maps or of ~~tyre~~tire characteristics or for the determination of the state of the roadway, as was previously thought necessary. The invention thus achieves aims which have long been pursued by those skilled in the art.

In order at the same time to achieve particularly good results, the features explained above and the features of the exemplary embodiments below can advantageously be employed singly or in combination, and additional advantageous effects may be obtained from the interaction of features according to the invention.

The invention will be explained in greater detail below with reference to exemplary embodiments, which are illustrated schematically in the figures and which reveal further following features and characteristics.

~~In the drawings:~~ **BRIEF DESCRIPTION OF THE DRAWINGS**

Fig. 1 ~~shows a diagram of the~~ illustrates an embodiment of a method for detecting the adhesion and the adhesion limit;

Fig. 2 ~~shows~~ illustrates an embodiment of a bound method for determining the state of the roadway;

Fig. 3 ~~shows~~ illustrates an embodiment of a tyre ~~tyre~~ characteristic diagram including five ~~tyre~~ tyre characteristics; and

5 Fig. 4 ~~shows~~ illustrates an embodiment of a high-precision adaptation of a ~~tyre~~ tyre characteristic.

DESCRIPTION OF EMBODIMENTS

As regards the meaning of the terms used in the text of this application,
10 attention is drawn to the following supplementary literature: DIN 70000; DIN 44300; J. Reimpell-K. Hoseus, Fahrwerktechnik: Fahrzeugmechanik [Suspension technology: Vehicle mechanics], Vogel Buchverlag 1992; A. Zomotor, Fahrwerktechnik: Fahrverhalten [Suspension technology: Handling], Vogel Buchverlag 1991. Although some of the terms used in these
15 literature references differ from one another slightly, the person skilled in the art will be able to allocate the correct meaning to them without difficulty.

Fig. 1 shows a flow diagram intended to illustrate more specifically an embodiment of the mode of operation of a system according to the invention for determining the adhesion and the adhesion limit for each individual wheel
20 of a vehicle. The word "adhesion" is here intended to denote the resultant of the circumferential force and the lateral force acting on the wheel, i.e. the adhesion is described by two forces or their resultants. The term "adhesion limit" is intended to denote the maximum possible circumferential force and lateral force which can be transmitted in the current driving state and with the
25 current roadway surface. The adhesion limit is thus described by two forces.

In this context, the circumferential force u is the component of the ground reaction force in the direction of the X_w axis (DIN 70000), i.e. obviously the force (motive or braking force) in the longitudinal direction of the wheel in the centre plane of the rim and in the plane of the roadway. The lateral force is the component of the ground reaction force in the direction of the Y_w axis (DIN 70000), i.e. obviously the force transverse to the wheel, perpendicular to the longitudinal direction of the wheel, in the plane of the roadway.

The system illustrated schematically in Fig. 1 performs two main tasks.

10 The left-hand part of the flow diagram shows system components used to calculate the current adhesion μ . The right-hand part shows the system components by means of which the current adhesion limit μ_{lim} is determined before this limit is reached. However, the adhesion limit μ_{lim} is not determined independently of the current adhesion μ . There is data exchange between the

15 left-hand part and the right-hand part.

The system comprises two groups of sensors. One group comprises driving-dynamics sensors 1, which supply data on the state of the vehicle as regards with respect to its driving dynamics. The other group comprises roadway sensors 2, which supply data on the state of the roadway.

20 The driving-dynamics sensors 1, some of which may already have been fitted as standard in the motor vehicle, supply, for example, measurement data on the longitudinal acceleration of the vehicle, the transverse acceleration, the roll angle, the pitch angle, the yaw angle, the rotational speeds of the individual wheels and the wheel loads of the

25 individual wheels.

It is also possible to determine individual variables indirectly, rather than measuring them directly. In general terms, it is possible to include in the method driving-dynamics variables derived from data measured by means of the driving-dynamics sensors. For example, it is possible for the yaw angle to
5 be determined by integrating the measured yaw rate or for the wheel load to be determined indirectly by measuring the compression travel of the wheels relative to the body rather than measuring the wheel load. It is also possible, for example, for measurement of the wheel loads of the wheels of an axle to be replaced by measurement of the axle load, which is apportioned to the
10 individual wheels using data from the driving-dynamics sensors 1, in particular the roll angle.

It is also possible, for example, for measurement of the wheel loads to be replaced by determination of the total weight. The total weight can be determined, for example, by measuring the drive torques and using the
15 measurement signals of the acceleration sensor in the longitudinal direction. In this case, it is possible, using data from the driving-dynamics sensors 1, in particular the pitch angle, to perform apportioning to the axle loads and, in particular by means of the roll angle, to perform apportioning to the individual wheel loads.

20 The data from the driving-dynamics sensors 1 and variables which may, if appropriate, have been derived indirectly therefrom are passed to the driving-dynamics simulation model 3, which is advantageously operated in real time. Real-time systems are distinguished by the fact that they can process external events within a predetermined time and thus comply with the
25 external time conditions (DIN 44300). This means that, in real-time simulation,

the calculated dynamic phenomenon corresponds at every point in time to the phenomenon which has actually occurred. There is no significant delay separating the behaviour of the real-time system from the behaviour of the real system.

5 Using the driving-dynamics simulation model 3, the circumferential forces currently acting on the individual wheels, the circumferential-slip values, the lateral forces and the slip angle are calculated. The term "circumferential slip" is here taken to mean the variable $S_{x,w}$ in accordance with DIN 70000, which clearly describes the slip between the ~~tyre~~tyre and the
10 roadway that occurs during braking or propulsion since, for the same vehicle speed, the wheel rotates more slowly during braking and more rapidly during propulsion than in the free-rolling state. According to DIN 70000, the slip angle is the angle between the X_w axis and the tangent to the curve of the path of the wheel contact point and describes clearly the angle between the
15 longitudinal direction of the wheel and the vector for the rate of travel of the centre of gravity of the wheel.

As the output variable, the driving-dynamics simulation model 3 supplies the current adhesion 4 for the individual wheels. The output data of the driving-dynamics simulation model 3 including the following variables -
20 longitudinal acceleration, transverse acceleration, roll angle, pitch angle, yaw angle, rotational speeds of the wheels and wheel loads - are also passed to the roadway detection component 5 and the characteristic adaptation component 6.

The roadway sensors 2 supply data on the temperature of the roadway
25 and/or on the state of the roadway, for example, using optical or acoustic

methods for example. It is also possible to employ sensors which give only a yes/no output, as to whether the roadway is dry or not for example.

The data from the roadway sensors 2 are processed by the roadway detector 5, which also receives results from the calculations by the driving-dynamics simulation model 3. These results of calculation are used for roadway detection if the current operating points in the tyretire characteristic are in the linear range of the circumferential-force/slip and lateral-force/slip-angle curves, i.e. if the vehicle is travelling with comparatively low longitudinal and transverse acceleration. Using the current operating points, it is possible in this case to determine the initial slope of the circumferential-force/slip and/or the lateral-force/slip-angle characteristic under consideration. In DIN 70000, the slope of the circumferential-force/slip curve is referred to as the circumferential-force/circumferential-slip gradient. The initial slope of the circumferential-force/slip curve is equivalent to the circumferential-force/circumferential-slip gradient at the circumferential force 0.

These initial slopes and data on the temperature of the roadway and the state of the roadway are thus available by optical or acoustic methods to allow the state of the roadway to be determined. The state of the roadway can then be identified using a bound method. Since there is at least partial redundancy in the state of the roadway in the identification of the state of the roadway, it is possible in many cases to carry out a plausibility check. If, for example, a large depth of water has been identified on the basis of the optical or acoustic methods, the temperature of the roadway should not simultaneously be very low. If this is nevertheless the case, it can be concluded from this that the roadway detector is faulty, and the system is

switched off. As an alternative, there is also the possibility of giving certain signals priority, the system thus remaining active and merely outputting a fault message.

If the roadway detector 5 is operating correctly, the state of the roadway determined is passed to a characteristic-map memory 7, preferably
5 and in one embodiment, the state of the roadway is passed separately for each wheel. The characteristic-map memory 7 furthermore receives information from the driving-dynamics sensors 1, in particular on the wheel load of the wheel for the selection of the appropriate tyretire characteristic.

10 To increase accuracy, further parameters can be taken into account, e.g. the influence of the camber angle. Since this is generally not measured in vehicles, it is possible to use a substitute dependency on a measured variable or on a combination of measured variables, e.g. wheel load and transverse acceleration. Finally, the information from the roadway detector 5 and the
15 driving-dynamics sensors 1 are used to select a suitable tyretire characteristic diagram (for different wheel loads, for example) and, from this, a suitable tyretire characteristic, preferably for each individual wheel separately.

The selected tyretire characteristic (or a tyretire characteristic diagram) is passed to the characteristic adaptor 6. Since the characteristic adaptor 6
20 also receives the output data from the driving-dynamics simulation model 3, it is possible to check whether the current adhesion 4 and the kinematic state of the individual wheels matches the selected tyretire characteristics. If this is not the case, the tyretire characteristic or the tyretire characteristic diagram is corrected by adapting individual characteristics, which are stored in the
25 characteristic-map memory 7.

However, the adaptation does not have to be limited to the selected tyretire characteristic 10; on the contrary, it is also possible while adapting one tyretire characteristic to adapt one or more further tyretire characteristics of one or more tyretire characteristic maps 9 accordingly. Adaptation of further, 5 so to speak "neighbouring", tyretire characteristics can be performed on the basis of theoretical or empirical knowledge of tyretire characteristic maps, for example.

One reason for this correction or adaptation can be that the properties of the tyrestires have changed over the period of operation of the vehicle, 10 owing to a decrease in tread depth for example. A change in the properties of the tyretire due to a tyretire change is also detected and corrected by the simulation calculation. If the current adhesion 4 differs from the selected tyretire characteristic, it is advantageously possible here for the correction or adaptation of the characteristic to be carried out approximately in normal 15 driving states and to be carried out with high precision in the vicinity of the driving limit, this being explained in conjunction with Fig. 4.

The characteristic adaptor 6 outputs tyretire characteristics which have been corrected or adapted for the wheels, these characteristics also being passed back to the characteristic-map memory 7 for storage. Since the 20 adhesion limit 8 is described by the maxima of the individual tyretire characteristics, it is thus known approximately when the vehicle is in a normal driving state. Insofar as the accuracy of characteristic adaptation is increased when the vehicle is approaching the driving limit, the adhesion limit is known with greater accuracy in the boundary zone.

Fig. 2 shows a table to explain in greater detail the procedure involved in roadway detection 5 using a bound method. In a bound method, the state of the roadway is not measured precisely but delimited by means of various pieces of information. For this purpose, information which allows conclusions to be drawn about the state of the roadway is gathered. The more information that is available, the more precisely the state of the roadway can be defined. Evaluating a single piece of information, it is possible for the state of the roadway to be delimited only very roughly at first. If further information is evaluated in addition, the delimitation becomes more and more precise, even if the individual pieces of information, considered on their own, allow only rough delimitation.

On the left-hand side of Fig. 2, there are lines listing information on the state of the roadway, it being possible for this information to stem from roadway sensors 2 or from the evaluation of the calculation using the driving-dynamics simulation model 3. This information preferably comprises at least three of the following types: air temperature, roadway temperature, optical or acoustic detection of snow, optical or acoustic detection of ice, optical or acoustic detection of water or optical or acoustic detection of a dry roadway. The particular pieces of information can, for example, be in the form of analogue measured variables, digital information (yes/no) or as a qualitative indication (deep, moderate, low).

The columns show, by way of example, various states of the roadway, which are assumed to be unknown and which are to be determined by the roadway detector 5. These states of the roadway can preferably include three

or more of the following: dry, damp, wet, shallow water, deep water, snow, ice, loose underlying surface.

If the measurement of the roadway temperature supplies the information "very low temperature", for example, and the roadway sensor for
5 detecting snow and ice supplies a positive signal and the evaluation of the initial slope of the circumferential-force/slip curve shows that the initial slope is shallow, the only possibility according to the pattern of crosses is that the roadway is covered in snow. This result is obtained even though a roadway
10 sensor 2 that detects specifically only the covering of the roadway by snow is not used. This bound system is furthermore redundant to a certain extent since, at least in some cases, the results can simply be checked. If, for instance, the sensor for determining roadway temperature fails in the example described, the covering of the roadway by snow can be identified by means of the two remaining pieces of information.

15 Fig. 3 shows a tyretire characteristic map 9 by way of example, the said map containing a plurality of tyretire characteristics 10 for various states of the roadway. A tyretire characteristic 10 is a curve in the tyretire characteristic map 9, and can be used to represent the circumferential force U as a function of the slip s or the lateral force as a function of the slip angle. In
20 general terms, a tyretire characteristic map 9 is a diagram in which a number of tyretire characteristics 10 for different parameters are illustrated. For example, the tyretire characteristic map 9 can illustrate circumferential-force/slip or lateral-force/slip-angle curves for various wheel loads, all the other parameters being held constant. Another possibility, as in Fig. 3, is
25 circumferential-force/slip curves for various roadway surfaces, for example.

~~Within the context of the invention~~ In one embodiment, the state of the roadway and/or the wheel load are preferably taken into account as the parameters of the tyretire characteristic 10 or tyretire characteristic map 9. Further or different advantageous parameters may be the transverse acceleration, the longitudinal acceleration, the rotational speed of the wheels
5 or the camber angle, for example.

It is advantageous if, when the system is first put into operation or after intentional resetting to initial values, for example, the tyretire characteristic maps 9 contain a basic set of characteristics 10 which does not as yet cover
10 all conceivable parameter combinations. The basic tyretire characteristics form a basic tyretire characteristic diagram in which tyretire characteristics for a small number of states of the roadway and/or wheel loads, for example, are stored in simplified general form. When the system is first put into operation, only a small number of basic tyretire characteristics can be stored for a small
15 number of different tyretire/roadway combinations. These characteristics apply to an average tyretire and do not accurately represent the behaviour of the tyretire actually fitted. Its actual behaviour depends, inter alia, on the type of tyretire, the state of the tread, the tyretire pressure and other parameters.

The basic characteristic maps are sufficient since a correction or
20 adaptation of the characteristics 10 stored is carried out in the system according to the invention. The state of the roadway is taken into account during this process. It is furthermore also advantageous if the tyretire characteristic maps 9 are supplemented by further tyretire characteristics 10. Parameter combinations that are lacking can here initially be covered by

interpolation, being replaced in the course of vehicle operation by their own tyretire characteristics 10.

It is advantageous if provision is made for the tyretire characteristic maps 9 to comprise at least three basic tyretire characteristics or tyretire characteristics 10 for the following states of the roadway: dry, damp, wet, shallow water, deep water, snow, ice, loose underlying surface. The effect of wheel load and the interaction between the circumferential and the lateral forces can be taken into account on the basis of empirical values, for example.

10 Since the actual behaviour of a tyretire does not coincide precisely with the behaviour described by the basic characteristics, the tyretire characteristics 10 and thus also the tyretire characteristic maps 9 are adapted during operation, a change in tyretire behaviour due, for example, to wear also being taken into account. As long as the operating states are normal, 15 with comparatively low longitudinal and transverse accelerations in combination with comparatively low circumferential-force/slip and slip-angle values, an approximate adaptation of the tyretire characteristics 10 can be performed as soon as a deviation between the current adhesion (in a kinematic state of the wheel) and the selected tyretire characteristic is 20 detected, and an approximate determination of the adhesion limit 8 can thus be carried out. This is possible even though the exact shape of the actual tyretire characteristic 10 in the range of high circumferential-force/slip and slip-angle values, i.e. comparatively high circumferential and/or lateral forces, is not yet known.

Fig. 4 illustrates how the adaptation of the tyretire characteristics 10 and the determination of the adhesion limit 8, 8a are carried out accurately in the region of the driving limit of the vehicle in accordance with a particularly advantageous feature of the invention. This highly accurate adaptation takes place as soon as the vehicle approaches the driving limit and the current adhesion 4 and the kinematic state of the wheels possibly no longer match the selected tyretire characteristic 10. As a result, the calculation of the adhesion limit 8 becomes more accurate as the vehicle approaches the driving limit.

10 The adaptation of the tyretire characteristic 10 can generally be performed as soon as deviations between the calculated current operating point 11 and the tyretire characteristic 10 originally selected from the characteristic-map memory 7 occur. In this context, the operating point 11 describes the driving state of a vehicle or a tyretire with which a particular
15 circumferential force U , a particular circumferential slip s , a particular lateral force and a particular slip angle can be associated. Within the context of the invention, the position of the operating point in a tyretire characteristic map 9 or on a tyretire characteristic 10 is not necessarily determined by measuring the circumferential force U and slip s or lateral force and slip angle directly,
20 the said variables instead being derived from the driving-dynamics simulation model 3, the selection of the tyretire characteristic 10 involving the roadway detector 5.

 The initial region 12 of the tyretire characteristic 10 can be regarded to a large extent as approximately linear. Particularly in the initial region, the

adaptation of the tyretire characteristic 10 or determination of the adhesion limit will be approximate.

At higher slip values, i.e. in the vicinity of the approximately applicable adhesion limit 8a, which is determined by the maximum of the tyretire characteristic 10 selected, the selected characteristic 10 leaves the linear region, however. In this region too, deviation of the selected characteristic 10 from the actually valid characteristic 14, from which the actual adhesion limit 8 can be determined, can be detected from the fact that the operating point 11 does not lie on the selected tyretire characteristic 10 but deviates from it. In the nonlinear case, this is the case for operating points 11 which lie above the deviation point 13.

The deviation point 13 is the point on the selected tyretire characteristic 10 from which the actually valid tyretire characteristic deviates from the selected tyretire characteristic 10 or from a linear shape in the direction of increasing slip or slip-angle values. The region from which the operating point 11 deviates from the tyretire characteristic 10 or from a linear shape is indicated in Fig. 4 by an upward-pointing arrow.

As soon as the operating point 11 no longer lies on the selected tyretire characteristic 10, the selected tyretire characteristic 10 is corrected, giving a new, corrected, tyretire characteristic 14. This adapted tyretire characteristic 14 then deviates, for example, from the originally selected characteristic 10, likewise from the deviation point 13. The adaptation can take place approximately already in the linear initial region. The detection of a deviation in conjunction with exact adaptation of the tyretire characteristic and determination of the adhesion limit is preferably possible when the linear initial

region 12 has been exceeded. However, exact adaptation of the tyretire characteristic and determination of the adhesion limit are possible not only in the immediate vicinity of the adhesion limit but are possible at a relatively early stage in the wider vicinity of the adhesion limit.

5 Deviation of the operating point 11 from the selected tyretire characteristic 10 or deviation of the tyretire characteristic 10 from the linear initial region can be used for sliding correction of the characteristic, each deviation being used for a correction. However, in many embodiments it can also be expedient if a correction is only carried out when the deviation
10 exceeds a particular threshold.

 When a deviation is detected, the selected tyretire characteristic 10 can be converted to a corrected tyretire characteristic 14, it being possible for this to be accomplished using the theoretical or empirical knowledge of neighbouring tyretire characteristics or of the fundamental behaviour of
15 vehicle tyrestires. Since adaptation of the tyretire characteristic 10 to give a corrected tyretire characteristic 14 can be performed more accurately particularly when the vehicle is approaching the driving limit, the accuracy of determination of the adhesion limit 8 is increased in the region of the adhesion limit 8 or driving limit.

20 In this way, approximate adaptation of the tyretire characteristic maps in operating situations involving comparatively low longitudinal and transverse accelerations and accurate adaptation of the tyretire characteristics during each approach to the driving limit is possible, irrespective of whether the driving situation is critical or not. During normal driving operation, the current
25 adhesion limit is estimated continuously in an approximate manner. When the

vehicle approaches the limiting range, determination of the current adhesion limit becomes more accurate. This means that precise data are available as soon as an exact intervention in the handling behaviour becomes necessary.

5 The invention provides reliable and accurate information on the current adhesion and the current adhesion limit before the adhesion limit has been reached. It is particularly advantageous here that not only the current adhesion limit but also the shape of the valid tyretire characteristic is available to allow extrapolation of the vehicle behaviour and, in the event of a vehicle control operation, optimum quality of control.

List of reference numerals

- ~~1~~Driving dynamics sensor
- ~~2~~Roadway sensor
- ~~3~~Driving dynamics simulation model
- ~~4~~Adhesion
- ~~5~~Roadway detector
- ~~6~~Characteristic adaptor
- ~~7~~Characteristic map memory
- ~~8~~Adhesion limit
- ~~8a~~Adhesion limit of the uncorrected tyre characteristic
- ~~9~~Tyre characteristic diagram
- ~~10~~Tyre characteristic
- ~~11~~Operating point
- ~~12~~Initial region
- ~~13~~Deviation point
- ~~14~~Corrected Tyre characteristic

U — Circumferential force

s — Slip

Patent Claims CLAIMS

1. ~~Method for determining the adhesion (4) and/or the adhesion limit (8) of a tyre of a vehicle in motion, comprising measuring the driving state of the vehicle by means of a plurality of driving dynamics sensors (1), determining the state of the roadway by means of at least one roadway sensor (2), which detects the state of the roadway, and evaluating the data of the driving dynamics sensors (1) and of the roadway sensor (2), a computer determining by means of a driving dynamics simulation model (3) the kinematic state of the wheel and the adhesion (4) and, taking into account at least one stored tyre characteristic diagram (9) comprising tyre characteristics (10), the adhesion limit (8), characterized in that, starting with an initial set of basic tyre characteristics, the tyre characteristics (10) are adapted in the course of operation to the current tyre behaviour.~~
2. ~~Method according to Claim 1, characterized in that adaptation of the tyre characteristics (10) takes place when a deviation from a tyre characteristic (10) is detected on the basis of a comparison of the results from the driving dynamics simulation model (3) and the determination of the state of the roadway.~~
3. ~~Method according to Claim 1 or 2, characterized in that the state of the roadway is determined by means of a plurality of different roadway sensors (2), the information derived from their signals being evaluated by means of a bound method for delimiting the state of the roadway.~~
4. ~~Method according to one of the preceding claims, characterized in that the roadway sensors (2) include at least three of the following types: air temperature, roadway temperature, optical or acoustic detection of snow or ice or water or a dry roadway.~~

5. ~~Method according to one of the preceding claims, characterized in that the tyre characteristic diagram (9) comprises tyre characteristics (10) in the form of circumferential force/slip and/or lateral force/slip-angle curves for particular states of the roadway and/or for different wheel loads.~~
6. ~~Method according to one of the preceding claims, characterized in that the tyre characteristic diagram (9) comprises at least three basic tyre characteristics or tyre characteristics (10) for the following states of the roadway: dry, damp, wet, shallow water, deep water, snow, ice, loose underlying surface.~~
7. ~~Method according to one of the preceding claims, characterized in that the tyre characteristic maps (9) comprise only a small total number of tyre characteristics (10), preferably less than 40, particularly preferably less than 20 tyre characteristics for determining the adhesion (4) and the adhesion limit (8).~~
8. ~~Method according to one of the preceding claims, characterized in that a tyre characteristic diagram (9) is supplemented in the course of operation by tyre characteristics (10) for further states of the roadway.~~
9. ~~Method according to one of the preceding claims, characterized in that, during the adaptation of one tyre characteristic (10), one or more further tyre characteristics of one or more tyre characteristic maps (9) is adapted accordingly.~~
10. ~~Method according to one of the preceding claims, characterized in that the bound method takes into account information from the driving dynamics simulation calculation.~~

- ~~11. Method according to one of the preceding claims, characterized in that the bound method takes account of the initial slope of the adhesion curve.~~
- ~~12. Method according to one of the preceding claims, characterized in that the adaptation of the tyre characteristics (10) is carried out in an approximate manner in the region of normal operating states of the vehicle and is carried out accurately in the region of the driving limit.~~
- ~~13. Method according to one of the preceding claims, characterized in that the determination of the adhesion limit (8) is carried out in an approximate manner in the region of normal operating states of the vehicle and is carried out accurately in the region of the driving limit.~~
- ~~14. Method according to Claim 12 or 13, characterized in that the accurate adaptation or determination is carried out when the linear initial region (12) of the selected tyre characteristic (10) has been exceeded.~~
- ~~15. Method according to Claim 12, 13 or 14, characterized in that the adaptation or determination is carried out when a calculated operating point (11) deviates from a selected tyre characteristic (10).~~
- ~~16. Method according to one of the preceding claims, characterized in that the driving dynamics simulation model (3) is a real-time model, by means of which the computer calculates the current kinematic state of the wheel and/or the current adhesion (4) and/or the current adhesion limit (8) of the wheel in real time.~~
- ~~17. Method according to one of the preceding claims, characterized in that the determination of the adhesion (4) and/or the adhesion limit (8) takes account of driving dynamics parameters which are derived from data measured by means of the driving dynamics sensors (1).~~

- ~~18. Method according to one of the preceding claims, characterized in that the adhesion (4) and/or the adhesion limit (8) is/are determined for each axle.~~
- ~~19. Method according to one of the preceding claims, characterized in that the adhesion and/or the adhesion limit of the entire vehicle is determined by means of the particular adhesion values (4) and/or adhesion limits (8) of all the wheels.~~
- ~~20. Apparatus for carrying out a method for determining the adhesion (4) and/or the adhesion limit (8) of a tyre of a vehicle in motion according to one of the preceding claims, comprising a plurality of driving dynamics sensors (1) for measuring the driving state of the vehicle, at least one roadway sensor (2), which detects the state of the roadway, for determining the state of the roadway and a computer for evaluating the data from the driving dynamics sensors (1) and the roadway sensor (2), the said computer using a driving dynamics simulation model (3) to determine the kinematic state of the wheel and the adhesion (4) and, taking into account at least one stored tyre characteristic diagram (9) comprising tyre characteristics (10), the adhesion limit (8), characterized in that the apparatus is designed to adapt the tyre characteristics (10) to the current tyre behaviour in the course of operation, starting from an initial set of basic tyre characteristics.~~
- ~~21. Apparatus according to Claim 20, characterized in that a plurality of different roadway sensors (2) for determining the state of the roadway is provided, and the computer is designed to delimit the state of the roadway, taking into account the information derived from the signals of the roadway sensors and using a bound method.~~

~~22. Method according to one of Claims 1-3, characterized in that the roadway sensors detect not only typical wet states of the roadway, such as ice, snow and water, but also properties of the underlying surface, especially roughness, nature of the material and/or an intermediate medium such as, in particular, oil, leaves or sand.~~

23. ~~Method according to Claim 22, characterized in that the tyre characteristic diagram (9) comprises basic characteristics or tyre characteristics (10) for various wet states of the roadway and/or properties of the underlying surface.~~
24. ~~Method according to one of Claims 1-5, characterized in that the tyre characteristic diagram (9) comprises tyre characteristics (10) in the form of circumferential force/slip and/or lateral force/ slip angle curves for different wheel speeds.~~
25. ~~Method according to one of Claims 1-17, characterized in that the adhesion (4) and/or the adhesion limit (8) is/are determined for each track or for each individual wheel.~~
26. ~~Method or apparatus according to one of the preceding claims, characterized in that a mathematical tyre model for generating the tyre characteristics is used to determine the adhesion and/or the adhesion limit instead of or as a supplement to a stored tyre characteristic diagram, the transition from one tyre characteristic to another being effected by changing one or more parameters of the tyre model.~~

Abstract

The invention proposes a method and an apparatus for determining the adhesion and/or adhesion limit of a tyretire of a vehicle, in which the data from driving-dynamics sensors are evaluated by means of a driving-dynamics simulation model and in which the evaluation of the data from roadway sensors takes into account tyretire characteristics which are adapted in the course of operation to the current tyretire behaviour. To delimit the state of the roadway, the information from the roadway sensors is preferably evaluated by means of a bound method.